

<b>STRUCTURAL BUILDING SYSTEM</b>	<b>VERSATILE STEEL SYSTEM</b>	<b>STANDARD STEEL SYSTEM</b>	<b>HEAVY-DUTY STEEL SYSTEM</b>	<b>LIGHT-WEIGHT ALUMINUM SYSTEM</b>	<b>ALL-PURPOSE ALUMINUM SYSTEM</b>
<b>Wiring Stud Construction</b>	<b>1 3/4" 16 Gauge Galvanealed Steel</b>	<b>3" 20 Gauge Galvanealed Steel</b>	<b>3" 16 Gauge Galvanealed Steel</b>	<b>1 3/4" 6063T-5 Extruded Aluminum</b>	<b>3" 6063T-5 Extruded Aluminum</b>
<b>INTERIOR: electrical &amp; data wiring raceway</b>	Friction-Fit Steel Cover Plates	Friction-Fit Steel Cover Plates	Friction-Fit Steel Cover Plates	Snap-in Aluminum Cover Plates	Snap-in Aluminum Cover Plates
<b>EXTERIOR: electrical &amp; data wiring raceway</b>	—	Friction-Fit Steel Cover Plates	Friction-Fit Steel Cover Plates	—	—
<b>LOAD BEARING:</b>					
<b>Smaller Footprint, Two Story</b>	●	—	●	—	●
<b>Wider Span, Two Story</b>	—	—	●	—	●
<b>Roof Load Capacity 50-125 lb per sq ft</b>	●	—	●	—	●
<b>Taller Wall Panels</b>	—	—	●	—	—
<b>Additional Insulation</b>	—	●	●	—	●
<b>Moisture Resistant</b>	—	—	—	●	●
<b>Outdoor Use</b>	—	—	—	—	●
<b>Finish</b>	Painted (custom or match standard Wall Panels: White, Gray, Beige)	Painted (custom or match standard Wall Panels: White, Gray, Beige)	Painted (custom or match standard Wall Panels: White, Gray, Beige)	Satin Anodized (silver) Custom Painting optional	Satin Anodized (silver) Custom Painting optional

<b>Corner Posts</b>	Extruded painted aluminum	Extruded satin anodized aluminum
<b>Wall Starters</b>	20 gauge painted galvanealed steel	Extruded satin anodized aluminum
<b>Ceiling Cap</b>	20 gauge painted galvanealed steel   Available in satin anodized aluminum	
<b>Ceiling Trim</b>	20 gauge painted galvanealed steel   Available in satin anodized aluminum	
<b>Floor Track</b>	24 gauge galvanealed steel; recommended for easier updates to Wall Panel   Available in aluminum	
<b>Base Molding</b>	Black Vinyl Base Molding; Interior & exterior base extends around outer corners concealing Floor Track	

### ROOFING OPTIONS

<b>Roof Decking</b>	Painted 22 gauge corrugated steel B-deck, 1 1/2" deep & cut to length. Overlays: OSB, plywood, tread plate
<b>Roof Storage</b>	Recessed I-beams on 48" centers, allows maximum load capacity of 125 lb per square foot
<b>Acoustical Ceiling</b>	White metal grid, hanger wire, and 5/8" thick 2x4' lay-in fiber board tiles. Additional materials may be used such as vinyl, drywall and more.

### ELECTRICAL COMPONENTS

<b>Switches &amp; Outlets</b>	Single Pole and 3-Way Switches, as well as Duplex Outlets are provided in a standard layout. Additions available.
<b>Breaker Panel</b>	125A circuit breaker panel, with 70A main breakers, & 15A individual breakers is standard. Can be upgraded as needed.
<b>Lighting</b>	T8 4-Lamp Lighting Fixtures with an acrylic lens (160Watt, 2x4 lay-in). Light bulbs are not included.
<b>Wiring Package</b>	Modular snap together wiring packages. RELOC Wiring Systems: Quick-Flex, OnePass, System 820



MANUFACTURING FACILITY: 436 Bussen Underground Road • Saint Louis, MO 63129  
toll free (800) 356-3199 | (314) 892-5800 | fax (314) 892-4070 | www.InPlant.com

**GROW ROOM OPTIONS**

<b>SPECIALIZED WALL PANELS</b>	<b>Material Layering</b>	<b>Sound Transmission Loss Contour</b>	<b>Additional Benefits</b>	<b>Sizes</b>	<b>Finish</b>
<b>1 3/4" Painted Gypsum Wall Panel</b>	1/2" Gypsum Polystyrene Core 1/2" Gypsum	<b>Noise Control</b> STC 31	UL Class 1 Non-combustible	44 7/8" width x 12' height	Standard Neutrals & Custom Paints
<b>3" Painted Gypsum Wall Panel</b>	1/2" Gypsum Polystyrene Core 1/2" Gypsum	<b>Noise Control</b> STC 32	UL Class 1 Non-combustible	44 7/8" width x 8'-26" height	Standard Neutrals & Custom Paints
<b>1 3/4" Steel Faced Wall Panel</b>	24 ga Steel & 1/2" Gypsum Polystyrene Core 1/2" Gypsum & 24 ga Steel	<b>Noise Control</b>	UL Class 1 Non-combustible, Galvanized, Laser Control	44 7/8" width x 12' height	Standard Neutrals & Custom Paints
<b>3" Steel Faced Wall Panel</b>	24 ga Steel & 1/2" Gypsum Polystyrene Core 1/2" Gypsum & 24 ga Steel	<b>Noise Control</b>	UL Class 1 Non-combustible, Galvanized, Laser Control	44 7/8" width x 8'-26" height	Standard Neutrals & Custom Paints
<b>1 3/4" Aluminum Faced Wall Panel</b>	.030 Aluminum (optional special 1/2" Gypsum) Polystyrene Core (optional special 1/2" Gypsum) 24 ga Steel or .030 Aluminum	<b>Noise Control</b>	UL Class 1 Non-combustible with Gypsum inclusion; Galvanized, Laser Control	44 7/8" width x 12' height	Standard Neutrals & Custom Paints
<b>3" Aluminum Faced Wall Panel</b>	.030 Aluminum (optional special 1/2" Gypsum) Polystyrene Core (optional special 1/2" Gypsum) .030 Aluminum	<b>Noise Control</b>	UL Class 1 Non-combustible with Gypsum inclusion; Galvanized, Laser Control	44 7/8" width x 8'-26" height	Standard Neutrals & Custom Paints
<b>3" Cement Board Wall Panel</b>	5/16" Cement Board Polystyrene Core 1/2" Gypsum/or Cement Board	<b>Noise Control</b>	UL Class 1 Non-combustible, Weather Resistant	44 7/8" width x 12' height	Standard Neutrals & Custom Paints
<b>1 3/4" FRP Faced Wall Panel</b>	Fiberglass Reinforced Plastic (optional special 1/2" Gypsum) Polystyrene Core (optional special 1/2" Gypsum) Fiberglass Reinforced Plastic	<b>Noise Control</b>	UL Class 1 Non-combustible with Gypsum inclusion; Moisture Control	44 7/8" width x 12' height	Standard Neutrals (White, Gray, Beige) Smooth or Textured
<b>3" FRP Faced Wall Panel</b>	Fiberglass Reinforced Plastic (optional special 1/2" Gypsum) Polystyrene Core (optional special 1/2" Gypsum) Fiberglass Reinforced Plastic	<b>Noise Control</b>	UL Class 1 Non-combustible with Gypsum inclusion; Moisture Control	44 7/8" width x 8'-26" height	Standard Neutrals (White, Gray, Beige) Smooth or Textured
<b>1 3/4" Vinyl Faced Gypsum Wall Panel</b>	6 mil Vinyl & 1/2" Gypsum Polystyrene Core 1/2" Gypsum & 6 mil Vinyl	<b>Noise Control</b> STC 31		44 7/8" width x 12' height	Vinyl Neutrals (White, Gray, Beige)
<b>3" Vinyl Faced Gypsum Wall Panel</b>	6 mil Vinyl & 1/2" Gypsum Polystyrene Core 1/2" Gypsum & 6 mil Vinyl	<b>Noise Control</b> STC 31		44 7/8" width x 8'-26" height	Vinyl Neutrals (White, Gray, Beige)
<b>1 3/4" Hardboard Wall Panel</b>	6 mil Vinyl & 1/8" Hardboard Polystyrene Core 1/8" Hardboard & 6 mil Vinyl	STC 24		44 7/8" width x 12' height	Vinyl Neutrals (White, Gray, Beige)
<b>3" Hardboard Wall Panel</b>	6 mil Vinyl & 1/8" Hardboard Polystyrene Core 1/8" Hardboard & 6 mil Vinyl	STC 24		44 7/8" width x 8'-26" height	Vinyl Neutrals (White, Gray, Beige)
<b>3" Soundstop™ Vinyl Wall Panel</b>	6 mil Vinyl & 5/8" Gypsum Rock Wool Fill 5/8" Gypsum * 6 mil Vinyl	<b>Soundstop™</b> STC 41	UL Class 1 Non-combustible, with Rock Wool Insulated Wiring Studs	44 7/8" width x 12' height	Vinyl Neutrals (White, Gray, Beige)
<b>3" Soundstop™ Steel Wall Panel</b>	24 ga Steel & 5/8" Gypsum Rock Wool Fill 5/8" Gypsum & 24 ga Steel	<b>Soundstop™</b> STC 43	UL Class 1 Non-combustible, with Rock Wool Insulated Wiring Studs	44 7/8" width x 8'-26" height	Standard Neutrals & Custom Paints

<b>Standard Doors &amp; Features</b>	3070 Steel Swing Door, 3' wide x 7' tall x 1 3/4" thick, insulated core (R-14), 20 gauge painted steel, 18 gauge steel frame; optional, 23 3/4" square door window of tempered glass. Hinges, Sweep, and a Key-in-knob Lock Set
<b>Custom Doors &amp; Features</b>	Custom sized Steel Swing Doors; Roll-up Door, manual or automated openers; Bumper Doors; Sliding & Strip Doors Conveyor openings; Framed openings for Shuttles, Turn-tables, and various Loading and Unloading Components
<b>Door Options</b>	Optional Interlocks and Key Card Devices. Lever Locks, Door Closer and Panic Exit Hardware are available
<b>Windows</b>	Pre-installed 1/4" tempered safety glass in anodized aluminum frames, 41" standard height; Custom window sizes
<b>Glass Alternatives</b>	Tinted or wire glass, acrylic or polycarbonate, bullet resistant and safety barrier glazing for welding and laser enclosures
<b>Frame Options</b>	Fixed, Sliding